MP SERIES MOTOR PUMPS

FOR TRASH AND CLEAN WATER

Whenever it is necessary to move large quantities of water, whether during flooding or simply filling a pond, these Petrol powered pumps can move it quickly and efficiently.

UP TO 1340 Lt/min FLOW





| ln | let. | Πı | tlet | Ρi | nes |
|----|------|----|------|----|-----|
| | | | | | |

| MOTOR PUMPS | MP36-2 | MP56-3 | MP34-2 | MP66-3 | | | | |
|---|------------|------------|------------|------------|--|--|--|--|
| PUMP | | | | | | | | |
| TYPE | Semitrash | Semitrash | Trash | Trash | | | | |
| HEAD m | 30 | 26 | 30 | 27 | | | | |
| FLOW L/min | 600 | 930 | 700 | 1340 | | | | |
| SPEED rpm | 3600 | 3600 | 3600 | 3600 | | | | |
| INPUT/OUTPUT DIAMETER inch | 2 | 3 | 2 | 3 | | | | |
| MAX DIAMETER ALLOWED mm | L | | 20 | 27 | | | | |
| ENGINE | | | LU | £7 | | | | |
| BRAND | Honda | Honda | Honda | Honda | | | | |
| MODEL | GX120 | GX160 | GX160 | GX240 | | | | |
| FUEL | Petrol | Petrol | Petrol | Petrol | | | | |
| DISPLACEMENT cc | 118 | 163 | 163 | 242 | | | | |
| CYLINDER | 1 inclined | 1 inclined | 1 inclined | 1 inclined | | | | |
| COOLING SYSTEM | Air | Air | Air | Air | | | | |
| STARTING SYSTEM / ELECTRIC CIRCUIT (Voit) | Recoil | Recoil | Recoil | Recoil | | | | |
| CONSUMPTION | | | | | | | | |
| CONSUMPTION at 75% of load L/h | 1,0 | 1,4 | 1,0 | 1,5 | | | | |
| TANK CAPACITY L | 2,0 | 3,1 | 3,1 | 5,3 | | | | |
| RUNNING TIME at 75% of load h | 2,0 | 2,2 | 3,1 | 3,5 | | | | |
| NOISE EMISSION | | | | | | | | |
| NOISE LEVEL LWA dB(A) | 103 | 105 | 106 | 110 | | | | |
| ACOUSTIC PRESSURE at 7 m dB(A) | 78 | 80 | 78 | 83 | | | | |
| DIMENSIONS AND WEIGHT | | | | | | | | |
| LENGTH mm | 437 | 477 | 520 | 690 | | | | |
| WIDTH mm | 364 | 416 | 462 | 485 | | | | |
| HEIGHT mm | 399 | 466 | 481 | 537 | | | | |
| WEIGHT (dry) Kg | 23 | 28 | 47 | 59 | | | | |
| STANDARD EQUIPMENT, OPTION AND ACCESSORIES (x: Standard, o: Optional) | | | | | | | | |
| OIL GUARD SYSTEM | x | X | X | X | | | | |
| 3 JUBILEE PIPE CLIPS | x | X | X | X | | | | |
| 2 THREADED COUPLINGS | X | X | X | X | | | | |
| FILTER | x | X | X | X | | | | |
| SPARK PLUG TOOL | X | X | X | X | | | | |
| INLET PIPES 2", 3" LENGTH 8/25 m | 0 | 0 | 0 | 0 | | | | |
| OUTLET PIPE 2", 3" LENGTH 5/10/50/100 m | 0 | 0 | 0 | 0 | | | | |
| | | | | | | | | |