


Cable lugs acc. to DIN 46235

DIN

- Material: 99,9% E-Cu DIN 40500
- Tube dimension acc. to DIN 46235 • Surface: tin-plated
- With marks for correct crimping
- Annealed material for easier crimping



Cu


Art. no.	CSS	M	ld.	d2	d1	d4	A	v1	v2	l	B	c1	c2	PU
290404	6	6	5	6,4	3,8	5,5	10,0	2	-	24,0	8,5	7,5	8,0	100
290406		8	5	8,4	3,8	5,5	10,0	2	-	24,0	13,0	10,0	10,0	100
290408	10	5	6	5,3	4,5	6,0	10,0	2	-	27,0	9,0	7,0	8,5	100
290410		6	6	6,4	4,5	6,0	10,0	2	-	27,0	9,0	7,5	8,5	100
290412		8	6	8,4	4,5	6,0	10,0	2	-	27,0	13,0	10,0	10,0	100
290414		10	6	10,5	4,5	6,0	10,0	2	-	28,0	15,0	10,0	10,0	100
290416	16	6	8	6,4	5,5	8,5	20,0	2	1	36,0	13,0	7,5	8,0	50
290418		8	8	8,4	5,5	8,5	20,0	2	1	36,0	13,0	10,0	10,0	50
290420		10	8	10,5	5,5	8,5	20,0	2	1	36,0	17,0	12,0	12,0	50
290422		12	8	13,0	5,5	8,5	20,0	2	1	36,0	18,0	13,0	13,0	50
290424	25	6	10	6,4	7,0	10,0	20,0	2	1	38,0	14,0	7,5	8,0	50
290426		8	10	8,4	7,0	10,0	20,0	2	1	38,0	16,0	10,0	10,0	50
290428		10	10	10,5	7,0	10,0	20,0	2	1	38,0	17,0	12,0	12,0	50
290430		12	10	13,0	7,0	10,0	20,0	2	1	38,0	19,0	13,0	13,0	50
290432	35	6	12	6,4	8,2	12,5	20,0	2	1	42,0	17,0	7,5	8,0	25
290434		8	12	8,4	8,2	12,5	20,0	2	1	42,0	17,0	10,0	10,0	25
290436		10	12	10,5	8,2	12,5	20,0	2	1	42,0	19,0	12,0	2,0	25
290438		12	12	13,0	8,2	12,5	20,0	2	1	42,0	21,0	13,0	13,0	25
290440	50	8	14	8,4	10,0	14,5	28,0	3	1	52,0	20,0	10,0	10,0	25
290442		10	14	10,5	10,0	14,5	28,0	3	1	52,0	22,0	12,0	12,0	25
290444		12	14	13,0	10,0	14,5	28,0	3	1	52,0	24,0	13,0	13,0	25
290446		16	14	17,0	10,0	14,0	28,0	3	1	52,0	28,0	16,0	16,0	20
290448	70	8	16	8,4	11,5	16,5	28,0	3	1	55,0	24,0	10,0	10,0	25
290450		10	16	10,5	11,5	16,5	28,0	3	1	55,0	24,0	12,0	12,0	25
290452		12	16	13,0	11,5	16,5	28,0	3	1	55,0	24,0	13,0	13,0	25
290454		16	16	17,0	11,5	16,5	28,0	3	1	55,0	30,0	16,0	16,0	20
290456	95	10	18	10,5	13,5	19,0	35,0	4	2	65,0	28,0	12,0	12,0	15
290458		12	18	13,0	13,5	19,0	35,0	4	2	65,0	28,0	13,0	13,0	15
290460		16	18	17,0	13,5	19,0	35,0	4	2	65,0	32,0	16,0	16,0	15
290462	120	10	20	10,5	15,5	21,0	35,0	4	2	70,0	32,0	15,0	16,0	20
290464		12	20	13,0	15,5	21,0	35,0	4	2	70,0	32,0	16,0	17,0	20
290466		16	20	17,0	15,5	21,0	35,0	4	2	70,0	32,0	19,0	20,0	20
290468		20	20	21,0	15,5	21,0	35,0	4	2	70,0	38,0	21,0	22,0	15
290470	150	10	22	10,5	17,0	23,5	35,0	4	2	78,0	34,0	15,0	16,0	15
290472		12	22	13,0	17,0	23,5	35,0	4	2	78,0	34,0	16,0	17,0	15
290474		16	22	17,0	17,0	23,5	35,0	4	2	78,0	34,0	19,0	20,0	15
290476		20	22	21,0	17,0	23,5	35,0	4	2	78,0	40,0	21,0	22,0	15
290478	185	10	25	10,5	19,0	25,5	40,0	4	2	82,0	37,0	15,0	16,0	10
290480		12	25	13,0	19,0	25,5	40,0	4	2	82,0	37,0	16,0	17,0	10
290482		16	25	17,0	19,0	25,5	40,0	4	2	82,0	37,0	19,0	20,0	10
290484		20	25	21,0	19,0	25,5	40,0	4	2	82,0	40,0	21,0	22,0	10
290486	240	12	28	13,0	21,5	29,0	40,0	5	2	92,0	42,0	16,0	17,0	8
290488		16	28	17,0	21,5	29,0	40,0	5	2	92,0	42,0	19,0	20,0	8
290490		20	28	21,0	21,5	29,0	40,0	5	2	92,0	45,0	21,0	22,0	8
290492	300	16	32	17,0	24,5	32,0	50,0	-	2	100,0	46,0	19,0	22,0	5
290494		20	32	21,0	24,5	32,0	50,0	-	2	100,0	46,0	19,0	22,0	5
290496	400	16	38	17,0	27,5	38,5	70,0	-	3	115,0	54,0	25,0	25,0	3
290498		20	38	21,0	27,5	38,5	70,0	-	3	115,0	54,0	25,0	25,0	1
290516	500	20	42	21,0	31,0	42,0	70,0	-	3	125,0	60,0	25,0	25,0	1
290518	625	20	44	21,0	34,5	44,0	80,0	-	3	125,0	64,0	25	25,0	1
290520	800	20	52	21,0	40,0	52,0	100,0	-	3	165	75,0	30,0	30,0	1
290522	1000	20	58	21,0	44,0	58,0	100,0	-	3	165,0	83,0	30,0	30,0	1



Cable lugs with 2 oval holes acc. to DIN 46235

DIN

- Material: 99,9% E-Cu DIN 40500
- Tube dimension acc. to DIN 46235 • Surface: tin-plated
- With marks for correct crimping • version with 2 oval holes
- Annealed material for easier crimping




Cu

Art. no.	CSS	M	ld.	d2	d1	d4	A	l	B	c1	c2	kg/100	PU
290550	70	12	16	13,0	11,5	16,5	28,0	55,0	24,0	13,0	13,0	10,800	25
290552	95	12	18	13,0	13,5	19,0	35,0	65,0	28,0	13,0	13,0	14,800	20
290554	120	12	20	13,0	15,5	21,0	35,0	70,0	32,0	16,0	17,0	18,600	25
290556	150	12	22	13,0	17,0	23,5	35,0	78,0	34,0	16,0	17,0	26,200	25
290558	185	12	25	13,0	19,0	25,5	40,0	82,0	37,0	16,0	17,0	26,800	10
290560	240	12	28	13,0	21,5	29,0	40,0	92,0	42,0	16,0	17,0	40,200	10

Angled cable lugs 90° acc. to DIN 46325

DIN

- Material: 99,9% E-Cu DIN 40500
- Tube dimension acc. to DIN 46235 • Surface: tin-plated
- With marks for correct crimping
- Annealed material for easier crimping




Cu

Art. no.	CSS	M	ld.	d2	d1	d4	A	v1	v2	B	c1	c2	kg/100	PU
291700	6	5	5	5,3	3,8	5,5	10,0	2	-	8,5	6,5	9,0	0,400	100
291702		6	5	6,4	3,8	5,5	10,0	2	-	8,5	7,5	10,0	0,300	100
291704	10	5	6	5,3	4,5	6,0	10,0	2	-	9,0	7,0	10,0	0,400	100
291706		6	6	6,4	4,5	6,0	10,0	2	-	9,0	7,5	10,0	0,500	100
291708		8	6	8,4	4,5	6,0	10,0	2	-	13,0	10,0	13,0	1,100	100
291710	16	6	8	6,4	5,5	8,5	20,0	2	1	13,0	7,5	11,0	1,200	50
291712		8	8	8,4	5,5	8,5	20,0	2	1	13,0	10,0	13,0	1,100	50
291714		10	8	10,5	5,5	8,5	20,0	2	1	17,0	12,0	15,0	1,200	50
291716		12	8	13,0	5,5	8,5	20,0	2	1	18,0	13,0	18,0	1,200	50
291718	25	6	10	6,4	7,0	10,0	20,0	2	1	14,0	7,5	11,0	1,500	50
291720		8	10	8,4	7,0	10,0	20,0	2	1	16,0	10,0	13,0	1,500	50
291722		10	10	10,5	7,0	10,0	20,0	2	1	17,0	12,0	15,0	1,500	50
291724		12	10	13,0	7,0	10,0	20,0	2	1	19,0	13,0	18,0	1,500	50
291726	35	8	12	8,4	8,2	12,5	20,0	2	1	17,0	10,0	13,0	2,600	25
291728		10	12	10,5	8,2	12,5	20,0	2	1	19,0	12,0	15,0	2,900	25
291730		12	12	13,0	8,2	12,5	20,0	2	1	21,0	13,0	18,0	2,900	25
291732	50	8	14	8,4	10,0	14,0	28,0	3	1	20,0	10,0	16,0	4,100	25
291734		10	14	10,5	10,0	14,0	28,0	3	1	22,0	12,0	16,0	4,200	20
291736		12	14	13,0	10,0	14,5	28,0	3	1	24,0	13,0	18,0	4,500	20
291738		16	14	17,0	10,0	14,5	28,0	3	1	28,0	16,0	22,0	4,100	20
291740	70	8	16	8,4	11,5	16,5	28,0	3	1	24,0	10,0	14,0	5,400	30
291742		10	16	10,5	11,5	16,5	28,0	3	1	24,0	12,0	16,0	5,500	30
291744		12	16	13,0	11,5	16,5	28,0	3	1	24,0	13,0	18,0	6,000	15
291746		16	16	17,0	11,5	16,5	28,0	3	1	30,0	16,0	22,0	5,600	30
291748	95	10	18	10,5	13,5	19,0	35,0	4	2	28,0	12,0	17,0	8,400	10
291750		12	18	13,0	13,5	19,0	35,0	4	2	28,0	13,0	18,0	8,700	10
291752		16	18	17,0	13,5	19,0	35,0	4	2	32,0	16,0	22,0	8,700	10
291754	120	10	20	10,5	15,5	21,0	35,0	4	2	32,0	15,0	17,0	10,000	20
291756		12	20	13,0	15,5	21,0	35,0	4	2	32,0	16,0	18,0	10,000	20
291758		16	20	17,0	15,5	21,0	35,0	4	2	32,0	18,0	22,0	10,200	20
291760		20	20	21,0	15,5	21,0	35,0	4	2	38,0	21,0	24,0	9,800	15
291762	150	10	22	10,5	17,0	23,5	35,0	4	2	34,0	15,0	17,0	13,100	15
291764		12	22	13,0	17,0	23,5	35,0	4	2	34,0	16,0	18,0	13,200	15
291766		16	22	17,0	17,0	23,5	35,0	4	2	34,0	19,0	22,0	14,100	15
291768		20	22	21,0	17,0	23,5	35,0	4	2	40,0	21,0	24,0	13,700	10
291770	185	10	25	10,5	19,0	25,5	40,0	4	2	37,0	15,0	22,0	16,400	10
291772		12	25	13,0	19,0	25,5	40,0	4	2	37,0	16,0	22,0	15,600	10
291774		16	25	17,0	19,0	25,5	40,0	4	2	37,0	19,0	22,0	18,600	10
291776		20	25	21,0	19,0	25,5	40,0	4	2	40,0	21,0	24,0	17,500	10
291778	240	12	28	13,0	21,5	29,0	40,0	5	2	42,0	16,0	22,0	22,400	10
291780		16	28	17,0	21,5	29,0	40,0	5	2	42,0	19,0	22,0	22,900	10
291782		20	28	21,0	21,5	29,0	40,0	5	2	45,0	21,0	24,0	21,000	10

Compression joints acc. to DIN 46267, Part 1 (for non-tension connections)

DIN

- Material: 99.9% E-CU DIN 40500 • Tube dimension acc. to DIN
- Surface: tin-plated • Annealed material for easier crimping
- For stranded conductors e.g. VDE 0295 class 2
- With buttmarks for precise cable insertion



Art. no.	CSS	ld.	d1	d4	v1	v2	TL	kg/100	PU
291521	6	5	3,8	5,5	2	-	30	0,300	1600
291523	10	6	4,5	6,0	2	-	30	0,600	1000
291525	16	8	5,5	8,5	2	1	50	1,450	300
291527	25	10	7,0	10,0	2	1	50	1,600	300
291529	35	12	8,2	12,5	2	1	50	3,000	200
291531	50	14	10,0	14,5	3	1	55	4,100	100
291533	70	16	11,5	16,5	3	1	55	5,400	100
291535	95	18	13,5	19,0	4	2	70	8,300	50
291537	120	20	15,5	21,0	4	2	70	9,500	50
291539	150	22	17,0	23,5	4	2	80	14,200	30
291541	185	25	19,0	25,5	4	2	85	16,900	30
291543	240	28	21,5	29,0	5	2	90	22,600	20
291545	300	32	24,5	32,0	-	2	100	29,700	10
291547	400	38	27,5	38,5	-	3	150	74,000	8
291549	500	42	31,0	42,0	-	3	160	89,100	5
291551	625	44	34,5	44,0	-	3	160	79,000	1
291553	800	52	40,0	52,0	-	3	200	151,300	1
291555	1000	58	44,0	58,0	-	3	1000	198,000	1

