



CoreLine Panel Generation 4 - For when light really matters

CoreLine Panel

CoreLine Panel Generation 4 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires, ready to directly replace functional luminaires in general lighting applications. CoreLine Panel innovative MultiColour/Lumen offers two colours of white and four lumen packages, all in one luminaire. And thanks to a new connector, installation is quick and easy.

Benefits

- The choice between warm and cool white, with different lumen outputs, in one single luminaire.
- New connector offers simpler and faster installation.
- Energy savings and longer lifetime, to reduce operating costs.

Features

- MultiColour/Lumen: 3000K and 4000K and different lumen output ranging from 3400 lumen to 4300 lumen in one single luminaire.
- Energy efficient and long lasting: up to 125lm/W and 50khrs L80 lifetime.
- Many drivers available: On/off (PSU), dimming (Dali) and integrated wireless connectivity (Interact Ready).
- Optional versions available: Emergency Lighting (EL) and Wieland/Adels connectors (W).

CoreLine Panel

Application


- Offices
- Retail
- Healthcare
- Education

Specifications

Type	RC132V (module size 600 mm version)
	RC133V (module size 625 mm version)
Ceiling type	Exposed T-bar ceiling
Ceiling grid	Module size in length: 600 mm
	Module size in length: 625 mm
Light source	Non-replaceable LED module
Power (+/-10%)	Standard version: 29 W
	High Lumen: 34.5 W
Beam angle	Standard version: 90°
	NOC version: 120°
Luminous flux	3400-4300 lm
Correlated Color	3000 K
Temperature	4000 K
Color Rendering Index	> 80
Lumen maintenance at median useful life*	L80
50000 h	

Control gear failure rate at median useful life	5%
50000 h	
Performance Ambient Temperature Tq	+25 °C
Operating temperature range	+10 to +40°C
Driver	Built-in
Mains voltage	230 or 240 V / 50-60 Hz
Material	Housing: Steel
	Optical cover: Polystyrene
Color	White (RAL 9003)
Connection	Quick connector or Wieland/Adels (W)
Maintenance	Optical module sealed for life; no internal cleaning required
Installation	Individual; lay-in in exposed ceiling grids
	No through-wiring possible
Remarks	Includes safety cable

Versions



CoreLine Panel - LED module
3600 lm - 840 neutral white -
Power supply unit with DALI
interface



CoreLine Panel - LED module
3600 lm - 840 neutral white -
Power supply unit with DALI
interface

CoreLine Panel


Product details




Edge View




PSD backcover Square



Dimming (PSD) Driver




Dimming (PSD) Connector



On/off (PSU) Connector



On/off (PSU) Driver




PSU backcover Square




On/off (PSU) Connector with hand

CoreLine Panel

Product details



PSU backcover Rectangular



PSD backcover Rectangular



On/off Multicolour/Lumen (PSU)
Driver



PSU MultiColour/Lumen backcover
Square



Panel_Acc-RC125Z_SMB_W60L60
-DPP.TIF




Surface mounted bracket



Surface mounted bracket



Surface mounted bracket



Panel_Acc-
RC125Z_SMB_W30L120 -DPP.TIF

CoreLine Panel

Product details



Safety cable



Safety cable



Safety cable



Plaster ceiling clips



Plaster ceiling clips



Plaster ceiling clips



Suspension set - On/Off driver (PSU)



Suspension set - On/Off driver (PSU)



Suspension set - On/Off driver (PSU)



Suspension set - Dali driver (PSD)



Suspension set - Dali driver (PSD)



Suspension set - Dali driver (PSD)

CoreLine Panel

Accessories



Surface Mounted kit

Ordercode 910930031018,
910930031118



CORELINE PANEL NOC ACC.

Ordercode 910930031218



Safety cable

Ordercode 911401892080



Plaster Ceiling Kit (PCV)

Ordercode 911401892180



Suspension set

Ordercode 911401892280,
911401892380

Application Conditions	
Ambient temperature range	+10 to +40 °C
Suitable for random switching	Not applicable
Approval and Application	
Mech. impact protection code	IK03
Ingress protection code	IP20/44
Operating and Electrical	
Input Voltage	220 to 240 V
General Information	
Beam angle of light source	– °
CE mark	CE mark
Protection class IEC	Safety class II
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	–
Light source replaceable	No
Number of gear units	1 unit
Initial Performance (IEC Compliant)	
Init. Color Rendering Index	>80
Luminous flux tolerance	+/-10%
Mechanical and Housing	
Color	White

Application Conditions

Order Code	Full Product Name	Maximum dim level
910505100532	RC132V G4 LED36S/840 PSD W60L60 OC ELB3	1%
910505100533	RC132V G4 LED36S/840 PSU W60L60 OC ELB3	1%
910505100541	RC132V G4 LED43S/840 PSD W60L60 OC ELB3	1%
910505100544	RC132V G4 LED36/840 PSU W60L60 OC TP(a)ELB3	Not applicable
910505100554	RC132V G4 LED36S/840 PSU W60L60 OC W3	Not applicable
910505100555	RC132V G4 LED34S/830 PSU W60L60 OC W3	Not applicable
910505100556	RC132V G4 LED36S/840 PSD W60L60 OC W5	1%
910505100564	RC132V G4 LED36_43S/830_840PSUW60L60OCW3	Not applicable
910505101186	RC132V G4 LED34S/830 WIA W60L60 NOC	1%
910505101187	RC132V G4 LED36S/840 WIA W60L60 OC	1%
910505101188	RC132V G4 LED34S/830 WIA W60L60 OC	1%
910505101278	RC132V G4 LED36S/840 WIA W60L60 NOC	1%
910505101284	RC133V G4 LED36S/840 WIA W62L62 NOC	1%
910505101285	RC133V G4 LED34S/830 WIA W62L62 NOC	1%
910505101286	RC133V G4 LED36S/840 WIA W62L62 OC	1%
910505101287	RC132V G4 LED43S/840 WIA W60L60 OC	1%
910505101288	RC133V G4 LED43S/840 WIA W62L62 OC	1%
910505101289	RC132V G4 LED43S/840 WIA W60L60 NOC	1%
910505101290	RC132V G4 LED43S/840 WIA W60L60 OC W3	1%
910505101291	RC132V G4 LED36S/840 WIA W60L60 NOC W3	1%
910505101292	RC132V G4 LED34S/830 WIA W60L60 NOC W3	1%
910505101293	RC132V G4 LED36S/840 WIA W60L60 OC W3	1%
910505101294	RC132V G4 LED34S/830 WIA W60L60 OC W3	1%
910505101297	RC132V G4 LED43S/840 WIA W60L60 NOC W3	1%
910505101298	RC132V G4 LED36/840 WIA W60L60 OC TP(a)	1%
911401877980	RC132V G4 LED36S/840 PSU W60L60 NOC	Not applicable
911401878080	RC132V G4 LED34S/830 PSU W60L60 NOC	Not applicable
911401878180	RC132V G4 LED43S/840 PSU W60L60 NOC	Not applicable
911401878280	RC133V G4 LED36S/840 PSU W62L62 NOC	Not applicable
911401878380	RC133V G4 LED34S/830 PSU W62L62 NOC	Not applicable
911401878580	RC132V G4 LED36S/840 PSU W60L60 OC	Not applicable
911401878680	RC132V G4 LED34S/830 PSU W60L60 OC	Not applicable
911401878780	RC133V G4 LED36S/840 PSU W62L62 OC	Not applicable
911401878980	RC132V G4 LED36S/840 PSD W60L60 OC	1%
911401879080	RC132V G4 LED34S/830 PSD W60L60 OC	1%
911401879180	RC132V G4 LED43S/840 PSD W60L60 OC	1%
911401879280	RC133V G4 LED36S/840 PSD W62L62 OC	1%
911401879380	RC133V G4 LED34S/830 PSD W62L62 OC	1%
911401879480	RC133V G4 LED43S/840 PSD W62L62 OC	1%
911401879780	RC132V G4 LED36/840 PSU W60L60 OC TP(a)	Not applicable
911401879880	RC132V G4LED34_43S/830_840 PSU W60L60 OC	Not applicable
911401879980	RC133V G4LED34_43S/830_840 PSU W62L62 OC	Not applicable
910505100536	RC132V G4 LED36S/840 PSU W30L120 OC ELB3	1%
910505100537	RC132V G4 LED36S/840 PSD W30L120 OC ELB3	1%
910505100560	RC132V G4LED36_43S/830_840PSUW30L120 OCW	Not applicable
910505101189	RC132V G4 LED36S/840 WIA W30L120 NOC	1%
910505101283	RC132V G4 LED36S/840 WIA W30L120 OC	1%
910505101295	RC132V G4 LED36S/840 WIA W30L120 NOC W3	1%
910505101296	RC132V G4 LED36S/840 WIA W30L120 OC W3	1%
911401878480	RC132V G4 LED36S/840 PSU W30L120 NOC	Not applicable
911401878880	RC132V G4 LED36S/840 PSU W30L120 OC	Not applicable

Order Code	Full Product Name	Maximum dim level
911401879580	RC132V G4 LED36S/840 PSD W30L120 OC	1%
911401879680	RC132V G4 LED34S/830 PSD W30L120 OC	1%
911401880080	RC132V G4LED34_43S/830_840 PSUW30L120 OC	Not applicable

Controls and Dimming

Order Code	Full Product Name	Dimmable
910505100532	RC132V G4 LED36S/840 PSD W60L60 OC ELB3	Yes
910505100533	RC132V G4 LED36S/840 PSU W60L60 OC ELB3	No
910505100541	RC132V G4 LED43S/840 PSD W60L60 OC ELB3	Yes
910505100544	RC132V G4 LED36/840 PSU W60L60 OC TP(a)ELB3	No
910505100554	RC132V G4 LED36S/840 PSU W60L60 OC W3	No
910505100555	RC132V G4 LED34S/830 PSU W60L60 OC W3	No
910505100556	RC132V G4 LED36S/840 PSD W60L60 OC W5	Yes
910505100564	RC132V G4 LED36_43S/830_840PSUW60L60OCW3	No
910505101186	RC132V G4 LED34S/830 WIA W60L60 NOC	Yes
910505101187	RC132V G4 LED36S/840 WIA W60L60 OC	Yes
910505101188	RC132V G4 LED34S/830 WIA W60L60 OC	Yes
910505101278	RC132V G4 LED36S/840 WIA W60L60 NOC	Yes
910505101284	RC133V G4 LED36S/840 WIA W62L62 NOC	Yes
910505101285	RC133V G4 LED34S/830 WIA W62L62 NOC	Yes
910505101286	RC133V G4 LED36S/840 WIA W62L62 OC	Yes
910505101287	RC132V G4 LED43S/840 WIA W60L60 OC	Yes
910505101288	RC133V G4 LED43S/840 WIA W62L62 OC	Yes
910505101289	RC132V G4 LED43S/840 WIA W60L60 NOC	Yes
910505101290	RC132V G4 LED43S/840 WIA W60L60 OC W3	Yes
910505101291	RC132V G4 LED36S/840 WIA W60L60 NOC W3	Yes
910505101292	RC132V G4 LED34S/830 WIA W60L60 NOC W3	Yes
910505101293	RC132V G4 LED36S/840 WIA W60L60 OC W3	Yes
910505101294	RC132V G4 LED34S/830 WIA W60L60 OC W3	Yes
910505101297	RC132V G4 LED43S/840 WIA W60L60 NOC W3	Yes
910505101298	RC132V G4 LED36/840 WIA W60L60 OC TP(a)	Yes
911401877980	RC132V G4 LED36S/840 PSU W60L60 NOC	No
911401878080	RC132V G4 LED34S/830 PSU W60L60 NOC	No

Order Code	Full Product Name	Dimmable
911401878180	RC132V G4 LED43S/840 PSU W60L60 NOC	No
911401878280	RC133V G4 LED36S/840 PSU W62L62 NOC	No
911401878380	RC133V G4 LED34S/830 PSU W62L62 NOC	No
911401878580	RC132V G4 LED36S/840 PSU W60L60 OC	No
911401878680	RC132V G4 LED34S/830 PSU W60L60 OC	No
911401878780	RC133V G4 LED36S/840 PSU W62L62 OC	No
911401878980	RC132V G4 LED36S/840 PSD W60L60 OC	Yes
911401879080	RC132V G4 LED34S/830 PSD W60L60 OC	Yes
911401879180	RC132V G4 LED43S/840 PSD W60L60 OC	Yes
911401879280	RC133V G4 LED36S/840 PSD W62L62 OC	Yes
911401879380	RC133V G4 LED34S/830 PSD W62L62 OC	Yes
911401879480	RC133V G4 LED43S/840 PSD W62L62 OC	Yes
911401879780	RC132V G4 LED36/840 PSU W60L60 OC TP(a)	No
911401879880	RC132V G4LED34_43S/830_840 PSU W60L60 OC	No
911401879980	RC133V G4LED34_43S/830_840 PSU W62L62 OC	No
910505100536	RC132V G4 LED36S/840 PSU W30L120 OC ELB3	No
910505100537	RC132V G4 LED36S/840 PSD W30L120 OC ELB3	Yes
910505100560	RC132V G4LED36_43S/830_840PSUW30L120 OCW	No
910505101189	RC132V G4 LED36S/840 WIA W30L120 NOC	Yes
910505101283	RC132V G4 LED36S/840 WIA W30L120 OC	Yes
910505101295	RC132V G4 LED36S/840 WIA W30L120 NOC W3	Yes
910505101296	RC132V G4 LED36S/840 WIA W30L120 OC W3	Yes
911401878480	RC132V G4 LED36S/840 PSU W30L120 NOC	No
911401878880	RC132V G4 LED36S/840 PSU W30L120 OC	No
911401879580	RC132V G4 LED36S/840 PSD W30L120 OC	Yes
911401879680	RC132V G4 LED34S/830 PSD W30L120 OC	Yes
911401880080	RC132V G4LED34_43S/830_840 PSUW30L120 OC	No

General Information

Order Code	Full Product Name	Product			
		Glow-wire test	Optic type	Family Code	Service tag
910505100532	RC132V G4 LED36S/840 PSD W60L60 OC ELB3	Temperature 850 °C, duration 30 s	Beam angle 90°	RC132V	No
910505100533	RC132V G4 LED36S/840 PSU W60L60 OC ELB3	Temperature 850 °C, duration 30 s	Beam angle 90°	RC132V	No
910505100541	RC132V G4 LED43S/840 PSD W60L60 OC ELB3	Temperature 850 °C, duration 30 s	Beam angle 90°	RC132V	No

Order Code	Full Product Name	Product			
		Glow-wire test	Optic type	Family Code	Service tag
910505100544	RC132V G4 LED36/840 PSU W60L60 OC TP(a)ELB3	Temperature 960 °C, duration 5 s	Beam angle 90°	RC132V	No
910505100554	RC132V G4 LED36S/840 PSU W60L60 OC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	No
910505100555	RC132V G4 LED34S/830 PSU W60L60 OC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	No

CoreLine Panel

Order Code	Full Product Name	Glow-wire test	Optic type	Product	
				Family Code	Service tag
910505100556	RC132V G4 LED36S/840 PSD W60L60 OC W5	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	No
910505100564	RC132V G4 LED36_43S/ 830_840PSUW60L60OCW3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	No
910505101186	RC132V G4 LED34S/830 WIA W60L60 NOC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101187	RC132V G4 LED36S/840 WIA W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101188	RC132V G4 LED34S/830 WIA W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101278	RC132V G4 LED36S/840 WIA W60L60 NOC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101284	RC133V G4 LED36S/840 WIA W62L62 NOC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC133V	-
910505101285	RC133V G4 LED34S/830 WIA W62L62 NOC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC133V	-
910505101286	RC133V G4 LED36S/840 WIA W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC133V	-
910505101287	RC132V G4 LED43S/840 WIA W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101288	RC133V G4 LED43S/840 WIA W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC133V	-
910505101289	RC132V G4 LED43S/840 WIA W60L60 NOC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101290	RC132V G4 LED43S/840 WIA W60L60 OC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101291	RC132V G4 LED36S/840 WIA W60L60 NOC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101292	RC132V G4 LED34S/830 WIA W60L60 NOC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101293	RC132V G4 LED36S/840 WIA W60L60 OC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-

Order Code	Full Product Name	Glow-wire test	Optic type	Product	
				Family Code	Service tag
910505101294	RC132V G4 LED34S/830 WIA W60L60 OC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101297	RC132V G4 LED43S/840 WIA W60L60 NOC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101298	RC132V G4 LED36/840 WIA W60L60 OC TP(a)	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
911401877980	RC132V G4 LED36S/840 PSU W60L60 NOC	Temperature 650 °C, duration 30 s	Beam angle 120°	-	No
911401878080	RC132V G4 LED34S/830 PSU W60L60 NOC	Temperature 650 °C, duration 30 s	Beam angle 120°	-	No
911401878180	RC132V G4 LED43S/840 PSU W60L60 NOC	Temperature 650 °C, duration 30 s	Beam angle 120°	-	No
911401878280	RC133V G4 LED36S/840 PSU W62L62 NOC	Temperature 650 °C, duration 30 s	Beam angle 120°	-	No
911401878380	RC133V G4 LED34S/830 PSU W62L62 NOC	Temperature 650 °C, duration 30 s	Beam angle 120°	-	No
911401878580	RC132V G4 LED36S/840 PSU W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401878680	RC132V G4 LED34S/830 PSU W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401878780	RC133V G4 LED36S/840 PSU W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401878980	RC132V G4 LED36S/840 PSD W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879080	RC132V G4 LED34S/830 PSD W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879180	RC132V G4 LED43S/840 PSD W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879280	RC133V G4 LED36S/840 PSD W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879380	RC133V G4 LED34S/830 PSD W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No

CoreLine Panel

Order Code	Full Product Name	Glow-wire test	Optic type	Product	
				Family Code	Service tag
911401879480	RC133V G4 LED43S/840 PSD W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879780	RC132V G4 LED36/840 PSU W60L60 OC TP(a)	Temperature 960 °C, duration 5 s	Beam angle 90°	-	No
911401879880	RC132V G4LED34_43S/ 830_840 PSU W60L60 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879980	RC133V G4LED34_43S/ 830_840 PSU W62L62 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
910505100536	RC132V G4 LED36S/840 PSU W30L120 OC ELB3	Temperature 850 °C, duration 30 s	Beam angle 90°	RC132V	No
910505100537	RC132V G4 LED36S/840 PSD W30L120 OC ELB3	Temperature 850 °C, duration 30 s	Beam angle 90°	RC132V	No
910505100560	RC132V G4LED36_43S/ 830_840PSUW30L120 OCW	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	No
910505101189	RC132V G4 LED36S/840 WIA W30L120 NOC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-

Order Code	Full Product Name	Glow-wire test	Optic type	Product	
				Family Code	Service tag
910505101283	RC132V G4 LED36S/840 WIA W30L120 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101295	RC132V G4 LED36S/840 WIA W30L120 NOC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
910505101296	RC132V G4 LED36S/840 WIA W30L120 OC W3	Temperature 650 °C, duration 30 s	Beam angle 90°	RC132V	-
911401878480	RC132V G4 LED36S/840 PSU W30L120 NOC	Temperature 650 °C, duration 30 s	Beam angle 120°	-	No
911401878880	RC132V G4 LED36S/840 PSU W30L120 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879580	RC132V G4 LED36S/840 PSD W30L120 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401879680	RC132V G4 LED34S/830 PSD W30L120 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No
911401880080	RC132V G4LED34_43S/ 830_840 PSUW30L120 OC	Temperature 650 °C, duration 30 s	Beam angle 90°	-	No

Initial Performance (IEC Compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminou flux	Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial LED luminaire efficacy	Initial luminous flux
910505100532	RC132V G4 LED36S/840 PSD W60L60 OC ELB3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	910505101187	RC132V G4 LED36S/840 WIA W60L60 OC	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
910505100533	RC132V G4 LED36S/840 PSU W60L60 OC ELB3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	910505101188	RC132V G4 LED34S/830 WIA W60L60 OC	(0.38, 0.38) SDCM <3	3000 K	117 lm/W	3400 lm
910505100541	RC132V G4 LED43S/840 PSD W60L60 OC ELB3	(0.38, 0.38) SDCM <3	4000 K	125 lm/W	4300 lm	910505101278	RC132V G4 LED36S/840 WIA W60L60 NOC	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
910505100544	RC132V G4 LED36/840 PSU W60L60 OC TP(a)ELB3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	910505101284	RC133V G4 LED36S/840 WIA W62L62 NOC	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
910505100554	RC132V G4 LED36S/840 PSU W60L60 OC W3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	910505101285	RC133V G4 LED34S/830 WIA W62L62 NOC	(0.38, 0.38) SDCM <3	3000 K	117 lm/W	3400 lm
910505100555	RC132V G4 LED34S/830 PSU W60L60 OC W3	(0.38, 0.38) SDCM <3	3000 K	117 lm/W	3400 lm	910505101286	RC133V G4 LED36S/840 WIA W62L62 OC	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
910505100556	RC132V G4 LED36S/840 PSD W60L60 OC W5	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	910505101287	RC132V G4 LED43S/840 WIA W60L60 OC	(0.38, 0.38) SDCM <3	4000 K	125 lm/W	4300 lm
910505100564	RC132V G4 LED36_43S/ 830_840PSUW60L60OCW3	(0.39, 0.39) SDCM ≤3	3000, 4000 K	125 lm/W	4300 lm	910505101288	RC133V G4 LED43S/840 WIA W62L62 OC	(0.38, 0.38) SDCM <3	4000 K	125 lm/W	4300 lm
910505101186	RC132V G4 LED34S/830 WIA W60L60 NOC	(0.38, 0.38) SDCM <3	3000 K	117 lm/W	3400 lm	910505101289	RC132V G4 LED43S/840 WIA W60L60 NOC	(0.38, 0.38) SDCM <3	4000 K	125 lm/W	4300 lm

CoreLine Panel

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial		Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Initial	
				LED efficacy	Initial luminous flux					LED efficacy	Initial luminous flux
910505101290	RC132V G4 LED43S/840 WIA W60L60 OC W3	(0.38, 0.38) SDCM <3	4000 K	125 lm/W	4300 lm	911401879380	RC133V G4 LED34S/830 PSD W62L62 OC	(0.44, 0.41) SDCM ≤3	3000 K	117 lm/W	3400 lm
910505101291	RC132V G4 LED36S/840 WIA W60L60 NOC W3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	911401879480	RC133V G4 LED43S/840 PSD W62L62 OC	(0.39, 0.39) SDCM ≤3	4000 K	125 lm/W	4300 lm
910505101292	RC132V G4 LED34S/830 WIA W60L60 NOC W3	(0.38, 0.38) SDCM <3	3000 K	117 lm/W	3400 lm	911401879780	RC132V G4 LED36/840 PSU W60L60 OC TP(a)	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm
910505101293	RC132V G4 LED36S/840 WIA W60L60 OC W3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	911401879880	RC132V G4LED34_43S/830_840 PSU W60L60 OC	(0.39, 0.39) SDCM ≤3	3000, 4000 K	125 lm/W	4300 lm
910505101294	RC132V G4 LED34S/830 WIA W60L60 OC W3	(0.38, 0.38) SDCM <3	3000 K	117 lm/W	3400 lm	911401879980	RC133V G4LED34_43S/830_840 PSU W62L62 OC	(0.39, 0.39) SDCM ≤3	3000, 4000 K	125 lm/W	4300 lm
910505101297	RC132V G4 LED43S/840 WIA W60L60 NOC W3	(0.38, 0.38) SDCM <3	4000 K	125 lm/W	4300 lm	910505100536	RC132V G4 LED36S/840 PSU W30L120 OC ELB3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
910505101298	RC132V G4 LED36/840 WIA W60L60 OC TP(a)	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm	910505100537	RC132V G4 LED36S/840 PSD W30L120 OC ELB3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
911401877980	RC132V G4 LED36S/840 PSU W60L60 NOC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm	910505100560	RC132V G4LED36_43S/830_840PSUW30L120 OCW	(0.39, 0.39) SDCM ≤3	3000, 4000 K	125 lm/W	4300 lm
911401878080	RC132V G4 LED34S/830 PSU W60L60 NOC	(0.44, 0.41) SDCM ≤3	3000 K	117 lm/W	3400 lm	910505101189	RC132V G4 LED36S/840 WIA W30L120 NOC	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
911401878180	RC132V G4 LED43S/840 PSU W60L60 NOC	(0.39, 0.39) SDCM ≤3	4000 K	125 lm/W	4300 lm	910505101283	RC132V G4 LED36S/840 WIA W30L120 OC	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
911401878280	RC133V G4 LED36S/840 PSU W62L62 NOC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm	910505101295	RC132V G4 LED36S/840 WIA W30L120 NOC W3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
911401878380	RC133V G4 LED34S/830 PSU W62L62 NOC	(0.44, 0.41) SDCM ≤3	3000 K	117 lm/W	3400 lm	910505101296	RC132V G4 LED36S/840 WIA W30L120 OC W3	(0.38, 0.38) SDCM <3	4000 K	123 lm/W	3600 lm
911401878580	RC132V G4 LED36S/840 PSU W60L60 OC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm	911401878480	RC132V G4 LED36S/840 PSU W30L120 NOC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm
911401878680	RC132V G4 LED34S/830 PSU W60L60 OC	(0.44, 0.41) SDCM ≤3	3000 K	117 lm/W	3400 lm	911401878880	RC132V G4 LED36S/840 PSU W30L120 OC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm
911401878780	RC133V G4 LED36S/840 PSU W62L62 OC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm	911401879580	RC132V G4 LED36S/840 PSD W30L120 OC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm
911401878980	RC132V G4 LED36S/840 PSD W60L60 OC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm	911401879680	RC132V G4 LED34S/830 PSD W30L120 OC	(0.44, 0.41) SDCM ≤3	3000 K	117 lm/W	3400 lm
911401879080	RC132V G4 LED34S/830 PSD W60L60 OC	(0.44, 0.41) SDCM ≤3	3000 K	117 lm/W	3400 lm	911401880080	RC132V G4LED34_43S/830_840 PSUW30L120 OC	(0.39, 0.39) SDCM ≤3	3000, 4000 K	125 lm/W	4300 lm
911401879180	RC132V G4 LED43S/840 PSD W60L60 OC	(0.39, 0.39) SDCM ≤3	4000 K	125 lm/W	4300 lm						
911401879280	RC133V G4 LED36S/840 PSD W62L62 OC	(0.38, 0.38) SDCM ≤3	4000 K	123 lm/W	3600 lm						

Initial Performance (IEC Compliant) (2/2)

Order Code	Full Product Name	Initial input power	Order Code	Full Product Name	Initial input power
910505100532	RC132V G4 LED36S/840 PSD W60L60 OC ELB3	33 W	910505100554	RC132V G4 LED36S/840 PSU W60L60 OC W3	29 W
910505100533	RC132V G4 LED36S/840 PSU W60L60 OC ELB3	33 W	910505100555	RC132V G4 LED34S/830 PSU W60L60 OC W3	29 W
910505100541	RC132V G4 LED43S/840 PSD W60L60 OC ELB3	37 W	910505100556	RC132V G4 LED36S/840 PSD W60L60 OC W5	29 W
910505100544	RC132V G4 LED36/840 PSU W60L60 OC TP(a)ELB3	29 W	910505100564	RC132V G4 LED36_43S/830_840PSUW60L60OCW3	30, 35 W

CoreLine Panel

Order Code	Full Product Name	Initial input power
910505101186	RC132V G4 LED34S/830 WIA W60L60 NOC	29 W
910505101187	RC132V G4 LED36S/840 WIA W60L60 OC	29 W
910505101188	RC132V G4 LED34S/830 WIA W60L60 OC	29 W
910505101278	RC132V G4 LED36S/840 WIA W60L60 NOC	29 W
910505101284	RC133V G4 LED36S/840 WIA W62L62 NOC	29 W
910505101285	RC133V G4 LED34S/830 WIA W62L62 NOC	29 W
910505101286	RC133V G4 LED36S/840 WIA W62L62 OC	29 W
910505101287	RC132V G4 LED43S/840 WIA W60L60 OC	29 W
910505101288	RC133V G4 LED43S/840 WIA W62L62 OC	34.5 W
910505101289	RC132V G4 LED43S/840 WIA W60L60 NOC	34.5 W
910505101290	RC132V G4 LED43S/840 WIA W60L60 OC W3	34.5 W
910505101291	RC132V G4 LED36S/840 WIA W60L60 NOC W3	29 W
910505101292	RC132V G4 LED34S/830 WIA W60L60 NOC W3	29 W
910505101293	RC132V G4 LED36S/840 WIA W60L60 OC W3	29 W
910505101294	RC132V G4 LED34S/830 WIA W60L60 OC W3	29 W
910505101297	RC132V G4 LED43S/840 WIA W60L60 NOC W3	34.5 W
910505101298	RC132V G4 LED36/840 WIA W60L60 OC TP(a)	29 W
911401877980	RC132V G4 LED36S/840 PSU W60L60 NOC	29 W
911401878080	RC132V G4 LED34S/830 PSU W60L60 NOC	29 W
911401878180	RC132V G4 LED43S/840 PSU W60L60 NOC	34.5 W
911401878280	RC133V G4 LED36S/840 PSU W62L62 NOC	29 W
911401878380	RC133V G4 LED34S/830 PSU W62L62 NOC	29 W
911401878580	RC132V G4 LED36S/840 PSU W60L60 OC	29 W

Order Code	Full Product Name	Initial input power
911401878680	RC132V G4 LED34S/830 PSU W60L60 OC	29 W
911401878780	RC133V G4 LED36S/840 PSU W62L62 OC	29 W
911401878980	RC132V G4 LED36S/840 PSD W60L60 OC	29 W
911401879080	RC132V G4 LED34S/830 PSD W60L60 OC	29 W
911401879180	RC132V G4 LED43S/840 PSD W60L60 OC	34.5 W
911401879280	RC133V G4 LED36S/840 PSD W62L62 OC	29 W
911401879380	RC133V G4 LED34S/830 PSD W62L62 OC	29 W
911401879480	RC133V G4 LED43S/840 PSD W62L62 OC	34.5 W
911401879780	RC132V G4 LED36/840 PSU W60L60 OC TP(a)	29 W
911401879880	RC132V G4LED34_43S/830_840 PSU W60L60 OC	30, 35 W
911401879980	RC133V G4LED34_43S/830_840 PSU W62L62 OC	30, 35 W
910505100536	RC132V G4 LED36S/840 PSU W30L120 OC ELB3	33 W
910505100537	RC132V G4 LED36S/840 PSD W30L120 OC ELB3	33 W
910505100560	RC132V G4LED36_43S/830_840PSUW30L120 OCW	30, 35 W
910505101189	RC132V G4 LED36S/840 WIA W30L120 NOC	29 W
910505101283	RC132V G4 LED36S/840 WIA W30L120 OC	29 W
910505101295	RC132V G4 LED36S/840 WIA W30L120 NOC W3	29 W
910505101296	RC132V G4 LED36S/840 WIA W30L120 OC W3	29 W
911401878480	RC132V G4 LED36S/840 PSU W30L120 NOC	29 W
911401878880	RC132V G4 LED36S/840 PSU W30L120 OC	29 W
911401879580	RC132V G4 LED36S/840 PSD W30L120 OC	29 W
911401879680	RC132V G4 LED34S/830 PSD W30L120 OC	29 W
911401880080	RC132V G4LED34_43S/830_840 PSUW30L120 OC	30, 35 W

