



ClearFlood Large – The best solution for 1:1 retrofit

ClearFlood Large

ClearFlood Large is designed to meet the requirements of a wide range of floodlighting applications. It also includes all the necessary control features and interfaces to make it future-proof and even more efficient. ClearFlood Large lets you choose the exact number of lumens you need for your application. Incorporating extremely high-efficiency optics and state-of-the-art LEDs, it is a highly competitive solution offering an outstanding lux/euro ratio and energy savings of up to 50% (without the use of additional controls). The wide choice of optics ensures maximum application coverage. ClearFlood Large is easy to install – you simply plug it in and select the best option for your needs. Perfect for replacing conventional technology and enabling intelligent lighting control while retaining the same electrical installation and poles. Tailor made solution : For tuned project solutions Philips can support with the exclusive L-Tune tool : build required flux to the best balance of life, maintained flux, energy, cost and product type.

Benefits

- Designed for 1:1 retrofit, perfect for replacing conventional technology retaining the same electrical installation and poles
- Offering a large variety of lighting needs from recreational sport, areas and even road and street, by providing a variety of optics used in the range
- Fast payback and low Total Cost of Ownership with energy savings and minimum maintenance costs
- Multiple control options ensure increased efficiency with intelligent lighting (DALI, CityTouch ready geolocalization)
- Equipped with Service tag, a QR-based identification system that makes each luminaire uniquely identifiable and provides maintenance, installation and spare part information

Features

- Designed for 1:1 retrofit up to 1000 W HID
- Wide range of lumen packages between 30 klm and 64 klm (system)
- Easy replacement of gear and PCB, no tooling required.
- Wide range of control options, such as CityTouch Ready, CLO, DALI, 1-10 V
- LEDs and optics deliver highest level of efficiency (up to 130 lm/W).
- 100% Philips components.
- Wide choice of optics to suit all applications – Sport and Areas lighting – Asymmetrical, Road and Symmetrical beams with or without louver (optional). New Asymmetrical Optic for Sport lighting (Tennis...)
- Optimized architecture for 4 kV surge (optional 10 kV).
- IP66 and IK08 protection.
- Long lifetime : 100 Khrs (L80B10 at T a 25°C)

Application

- Airports
- Harbors
- Large recreational sports facilities
- Industrial areas
- Roundabouts and motorway junctions

Specifications

Type	BVP651:LEDxxx-4S
	BVP651i: additional options via configurator
Light source	Integral LED-module
Power	Up to 553 W (+/- 11%) all CCT
Luminous flux	Up to 62000 lm (NW/CW) (-/+7%)
Luminaire efficacy	Up to 130 lm/W (NW/CW)
Correlated Color	3000, 4000 or 5700 K
Temperature	
Color Rendering Index	80 / 70 / 70
Lumen maintenance at median useful life*	up to L93
100000 h	
Control gear failure rate at median useful life	10%
100000 h	
Performance Ambient Temperature Tq	+25 °C
Operating temperature range	-40 to +45 °C
Driver	Built-in (self-ballasted LED-module) - NTC
Mains voltage	220-240 V AC / 50-60 Hz
Power factor	>0.95
Surge protection	4 kV as standard, 10 kV as option
Dimming	Dimming via external communication (DALI)
	Dimming via mains voltage (AmpDim)
	Dimming via DynaDimmer (5 steps)
	Constant Light Output (CLO)
	CityTouch ready; GPRS antenna
Controls system input	DALI

Options	Class I or II
	(MSP) Marine salt protection - 1000 h
	(SPO) Swimming Pool Protection
Optic	Asymmetrical, symmetrical and road optics
Optical element	Louver for limited backlight cut-off (BL1 and BL2)
Optical cover	Clear tempered flat glass
Material	Die-cast aluminum
Color	RAL9007 matt
Connection	Mains power via a waterproof connector (supplied) mounted on the projector and accepting cable diameters between 10 to 14 mm
	External control command DALI (D9), via the supplied waterproof connector (same as the mains supply) accepting cable diameters from 10 mm to 14 mm, or cable entry via 2 waterproof connectors supplied (in DALI / DALI out)
Maintenance	No internal cleaning required
	Direct access to LED engine modules and drivers
	Gear replacement can be asked via options
	Spare part list available (glass, optics, bracket, protractor scale, PCB LED, connector)

ClearFlood Large

Installation	U-shaped mounting bracket with foot-print suitable for 3-point fixation by means of M20 bolts
	Vertical aiming from the horizontal: -90° / +90°, memory cap
	Standing-up or hanging-down mounting /U-bracket stirrup with standard bolts and nuts
	Protractor scale with intervals of 5°, memory cap
	Ready for CityTouch (based on DALI protocol) with external tray fixed on the bracket

	Projected area in horizontal position: at 0° 0.05 SCx: at 90° : 0.41 m², at 0° : 0.05 m², at 15° : 0.13 m²
	Max adjustment from the horizontal: -170 to +170°
Cable gland	External IP67 waterproof, plug-in connector (5-pin)
Remarks	CE, ENEC, RoHS, VDE-Ball proof

Versions



Product details



OPDP_BVP650i_0013-Detail photo



OPDP_BVP650i_0017-Detail photo



ClearFlood Large

Product details



Clearflood Large CityTouch-DPP.jpg

Approval and Application

Mech. impact protection code	IK08
Surge Protection (Common/Differential)	Luminaire surge protection level until 4 kV differential mode and 4 kV common mode

Controls and Dimming

Dimmable	No
----------	----

General Information

CE mark	CE mark
Light source color	740 neutral white
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Light source replaceable	Yes
Number of gear units	2 units
Product Family Code	BVP651

Initial Performance (IEC Compliant)

Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	70

Light Technical

Standard tilt angle side entry	0°
Standard tilt angle posttop	0°
Upward light output ratio	0

General Information (1/2)

Order Code	Full Product Name	Luminaire light beam spread	Optical cover/lens type	Lamp family code	Lamp version
912300023731	BVP651 LED450-4S/740 S ALU PSU	70° x 21°	Flat glass	LED450	-
912300023732	BVP651 LED450-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED450	-
912300023733	BVP651 LED450-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED450	-
912300023734	BVP651 LED450-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED450	-
912300023735	BVP651 LED450-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED450	-
912300023736	BVP651 LED450-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED450	-
912300023737	BVP651 LED450-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED450	-
912300023738	BVP651 LED500-4S/740 S ALU PSU	70° x 21°	Flat glass	LED500	-
912300023739	BVP651 LED500-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED500	-
912300023740	BVP651 LED500-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED500	-
912300023741	BVP651 LED500-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED500	-
912300023742	BVP651 LED500-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED500	-
912300023743	BVP651 LED500-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED500	-
912300023744	BVP651 LED500-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED500	-
912300023745	BVP651 LED550-4S/740 S ALU PSU	70° x 21°	Flat glass	LED550	-
912300023746	BVP651 LED550-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED550	-
912300023747	BVP651 LED550-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED550	-

Order Code	Full Product Name	Luminaire light beam spread	Optical cover/lens type	Lamp family code	Lamp version
912300023748	BVP651 LED550-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED550	-
912300023749	BVP651 LED550-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED550	-
912300023750	BVP651 LED550-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED550	-
912300023751	BVP651 LED550-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED550	-
912300023752	BVP651 LED600-4S/740 S ALU PSU	70° x 21°	Flat glass	LED600	-
912300023753	BVP651 LED600-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED600	-
912300023754	BVP651 LED600-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED600	-
912300023755	BVP651 LED600-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED600	-
912300023756	BVP651 LED600-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED600	-
912300023757	BVP651 LED600-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED600	-
912300023758	BVP651 LED600-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED600	-
912300023759	BVP651 LED650-4S/740 S ALU PSU	70° x 21°	Flat glass	LED650	-
912300023760	BVP651 LED650-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED650	-
912300023761	BVP651 LED650-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED650	-
912300023762	BVP651 LED650-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED650	-
912300023763	BVP651 LED650-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED650	-
912300023764	BVP651 LED650-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED650	-
912300023765	BVP651 LED650-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED650	-
912300023766	BVP651 LED700-4S/740 S ALU PSU	70° x 21°	Flat glass	LED700	-
912300023767	BVP651 LED700-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED700	-
912300023768	BVP651 LED700-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED700	-
912300023769	BVP651 LED700-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED700	-
912300023770	BVP651 LED700-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED700	-
912300023771	BVP651 LED700-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED700	-
912300023772	BVP651 LED700-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED700	-

Order Code	Full Product Name	Luminaire light beam spread	Optical cover/lens type	Lamp family code	Lamp version
912300023793	BVP651 LED750-4S/740 S ALU PSU	70° x 21°	Flat glass	LED750	-
912300023794	BVP651 LED750-4S/740 OFA52 ALU PSU	39° - 11° x 98°	Flat glass	LED750	-
912300023795	BVP651 LED750-4S/740 DM10 ALU PSU	157° x 111°	Flat glass	LED750	-
912300023796	BVP651 LED750-4S/740 DW10 ALU PSU	52° - 7° x 151°	Flat glass	LED750	-
912300023797	BVP651 LED750-4S/740 DX10 ALU PSU	20° - 4° x 150°	Flat glass	LED750	-
912300023798	BVP651 LED750-4S/740 DX50 ALU PSU	17° - 5° x 132°	Flat glass	LED750	-
912300023799	BVP651 LED750-4S/740 DX51 ALU PSU	14° - 5° x 132°	Flat glass	LED750	-
912300023961	BVP651 LED450-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED450	-
912300023962	BVP651 LED500-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED500	-
912300023963	BVP651 LED550-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED550	-
912300023964	BVP651 LED600-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED600	-
912300023965	BVP651 LED650-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED650	-
912300023966	BVP651 LED700-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED700	-
912300023967	BVP651 LED750-4S/740 DX60 ALU PSU	8° - 26° x 82°	Flat glass	LED750	-
912300024506	BVP651 LED800-4S/740 PSU DX60 ALU	8° - 26° x 82°	Glass	LED800	4S
912300024507	BVP651 LED800-4S/740 PSU DX51 ALU	14° - 5° x 132°	Glass	LED800	4S
912300024508	BVP651 LED800-4S/740 PSU DX50 ALU	17° - 5° x 132°	Glass	LED800	4S
912300024509	BVP651 LED800-4S/740 PSU DX10 ALU	20° - 4° x 150°	Glass	LED800	4S
912300024510	BVP651 LED800-4S/740 PSU OFA52 ALU	39° - 11° x 98°	Glass	LED800	4S
912300024511	BVP651 LED800-4S/740 PSU S ALU	70° x 21°	Glass	LED800	4S
912300024512	BVP651 LED800-4S/740 PSU DM10 ALU	157° x 111°	Glass	LED800	4S
912300024513	BVP651 LED800-4S/740 PSU DW10 ALU	52° - 7° x 151°	Glass	LED800	4S

General Information (2/2)

ClearFlood Large

Order Code	Full Product Name	Optic type	Service tag
912300023731	BVP651 LED450-4S/740 S ALU PSU	Symmetrical	-
912300023732	BVP651 LED450-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023733	BVP651 LED450-4S/740 DM10 ALU PSU	Distribution medium 10	Yes
912300023734	BVP651 LED450-4S/740 DW10 ALU PSU	Distribution wide 10	-
912300023735	BVP651 LED450-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023736	BVP651 LED450-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023737	BVP651 LED450-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023738	BVP651 LED500-4S/740 S ALU PSU	Symmetrical	-
912300023739	BVP651 LED500-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023740	BVP651 LED500-4S/740 DM10 ALU PSU	Distribution medium 10	-
912300023741	BVP651 LED500-4S/740 DW10 ALU PSU	Distribution wide 10	-
912300023742	BVP651 LED500-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023743	BVP651 LED500-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023744	BVP651 LED500-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023745	BVP651 LED550-4S/740 S ALU PSU	Symmetrical	-
912300023746	BVP651 LED550-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023747	BVP651 LED550-4S/740 DM10 ALU PSU	Distribution medium 10	-
912300023748	BVP651 LED550-4S/740 DW10 ALU PSU	Distribution wide 10	-
912300023749	BVP651 LED550-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023750	BVP651 LED550-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023751	BVP651 LED550-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023752	BVP651 LED600-4S/740 S ALU PSU	Symmetrical	-
912300023753	BVP651 LED600-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023754	BVP651 LED600-4S/740 DM10 ALU PSU	Distribution medium 10	-
912300023755	BVP651 LED600-4S/740 DW10 ALU PSU	Distribution wide 10	-

Order Code	Full Product Name	Optic type	Service tag
912300023756	BVP651 LED600-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023757	BVP651 LED600-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023758	BVP651 LED600-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023759	BVP651 LED650-4S/740 S ALU PSU	Symmetrical	-
912300023760	BVP651 LED650-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023761	BVP651 LED650-4S/740 DM10 ALU PSU	Distribution medium 10	-
912300023762	BVP651 LED650-4S/740 DW10 ALU PSU	Distribution wide 10	-
912300023763	BVP651 LED650-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023764	BVP651 LED650-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023765	BVP651 LED650-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023766	BVP651 LED700-4S/740 S ALU PSU	Symmetrical	-
912300023767	BVP651 LED700-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023768	BVP651 LED700-4S/740 DM10 ALU PSU	Distribution medium 10	-
912300023769	BVP651 LED700-4S/740 DW10 ALU PSU	Distribution wide 10	-
912300023770	BVP651 LED700-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023771	BVP651 LED700-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023772	BVP651 LED700-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023793	BVP651 LED750-4S/740 S ALU PSU	Symmetrical	-
912300023794	BVP651 LED750-4S/740 OFA52 ALU PSU	Optiflux asymmetrical axis angle 52°	-
912300023795	BVP651 LED750-4S/740 DM10 ALU PSU	Distribution medium 10	-
912300023796	BVP651 LED750-4S/740 DW10 ALU PSU	Distribution wide 10	-
912300023797	BVP651 LED750-4S/740 DX10 ALU PSU	Distribution extra wide 10	-
912300023798	BVP651 LED750-4S/740 DX50 ALU PSU	Distribution extra wide 50	-
912300023799	BVP651 LED750-4S/740 DX51 ALU PSU	Distribution extra wide 51	-
912300023961	BVP651 LED450-4S/740 DX60 ALU PSU	Distribution extra wide 60	-

ClearFlood Large

Order Code	Full Product Name	Optic type	Service tag
912300023962	BVP651 LED500-4S/740 DX60 ALU PSU	Distribution extra wide 60	-
912300023963	BVP651 LED550-4S/740 DX60 ALU PSU	Distribution extra wide 60	-
912300023964	BVP651 LED600-4S/740 DX60 ALU PSU	Distribution extra wide 60	-
912300023965	BVP651 LED650-4S/740 DX60 ALU PSU	Distribution extra wide 60	-
912300023966	BVP651 LED700-4S/740 DX60 ALU PSU	Distribution extra wide 60	-
912300023967	BVP651 LED750-4S/740 DX60 ALU PSU	Distribution extra wide 60	-
912300024506	BVP651 LED800-4S/740 PSU DX60 ALU	Distribution extra wide 60	-

Order Code	Full Product Name	Optic type	Service tag
912300024507	BVP651 LED800-4S/740 PSU DX51 ALU	Distribution extra wide 51	-
912300024508	BVP651 LED800-4S/740 PSU DX50 ALU	Distribution extra wide 50	-
912300024509	BVP651 LED800-4S/740 PSU DX10 ALU	Distribution extra wide 10	-
912300024510	BVP651 LED800-4S/740 PSU OFA52 ALU	Optiflux asymmetrical axis angle 52°	-
912300024511	BVP651 LED800-4S/740 PSU S ALU	Symmetrical	-
912300024512	BVP651 LED800-4S/740 PSU DM10 ALU	Distribution medium 10	-
912300024513	BVP651 LED800-4S/740 PSU DW10 ALU	Distribution wide 10	-

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial luminous flux
912300023731	BVP651 LED450-4S/740 S ALU PSU	39150 lm
912300023732	BVP651 LED450-4S/740 OFA52 ALU PSU	38700 lm
912300023733	BVP651 LED450-4S/740 DM10 ALU PSU	38250 lm
912300023734	BVP651 LED450-4S/740 DW10 ALU PSU	38250 lm
912300023735	BVP651 LED450-4S/740 DX10 ALU PSU	36900 lm
912300023736	BVP651 LED450-4S/740 DX50 ALU PSU	37350 lm
912300023737	BVP651 LED450-4S/740 DX51 ALU PSU	22500 lm
912300023738	BVP651 LED500-4S/740 S ALU PSU	43000 lm
912300023739	BVP651 LED500-4S/740 OFA52 ALU PSU	42500 lm
912300023740	BVP651 LED500-4S/740 DM10 ALU PSU	42000 lm
912300023741	BVP651 LED500-4S/740 DW10 ALU PSU	42000 lm
912300023742	BVP651 LED500-4S/740 DX10 ALU PSU	40500 lm
912300023743	BVP651 LED500-4S/740 DX50 ALU PSU	41000 lm
912300023744	BVP651 LED500-4S/740 DX51 ALU PSU	25000 lm
912300023745	BVP651 LED550-4S/740 S ALU PSU	48160 lm
912300023746	BVP651 LED550-4S/740 OFA52 ALU PSU	47600 lm
912300023747	BVP651 LED550-4S/740 DM10 ALU PSU	47040 lm
912300023748	BVP651 LED550-4S/740 DW10 ALU PSU	47040 lm
912300023749	BVP651 LED550-4S/740 DX10 ALU PSU	45360 lm
912300023750	BVP651 LED550-4S/740 DX50 ALU PSU	45920 lm
912300023751	BVP651 LED550-4S/740 DX51 ALU PSU	28000 lm
912300023752	BVP651 LED600-4S/740 S ALU PSU	51600 lm
912300023753	BVP651 LED600-4S/740 OFA52 ALU PSU	51000 lm
912300023754	BVP651 LED600-4S/740 DM10 ALU PSU	50400 lm
912300023755	BVP651 LED600-4S/740 DW10 ALU PSU	50400 lm
912300023756	BVP651 LED600-4S/740 DX10 ALU PSU	48600 lm
912300023757	BVP651 LED600-4S/740 DX50 ALU PSU	49200 lm
912300023758	BVP651 LED600-4S/740 DX51 ALU PSU	30000 lm
912300023759	BVP651 LED650-4S/740 S ALU PSU	56100 lm
912300023760	BVP651 LED650-4S/740 OFA52 ALU PSU	55440 lm
912300023761	BVP651 LED650-4S/740 DM10 ALU PSU	54780 lm
912300023762	BVP651 LED650-4S/740 DW10 ALU PSU	55440 lm

Order Code	Full Product Name	Initial luminous flux
912300023763	BVP651 LED650-4S/740 DX10 ALU PSU	52800 lm
912300023764	BVP651 LED650-4S/740 DX50 ALU PSU	53460 lm
912300023765	BVP651 LED650-4S/740 DX51 ALU PSU	32340 lm
912300023766	BVP651 LED700-4S/740 S ALU PSU	59500 lm
912300023767	BVP651 LED700-4S/740 OFA52 ALU PSU	58800 lm
912300023768	BVP651 LED700-4S/740 DM10 ALU PSU	58100 lm
912300023769	BVP651 LED700-4S/740 DW10 ALU PSU	58800 lm
912300023770	BVP651 LED700-4S/740 DX10 ALU PSU	56000 lm
912300023771	BVP651 LED700-4S/740 DX50 ALU PSU	56700 lm
912300023772	BVP651 LED700-4S/740 DX51 ALU PSU	34300 lm
912300023793	BVP651 LED750-4S/740 S ALU PSU	64600 lm
912300023794	BVP651 LED750-4S/740 OFA52 ALU PSU	63840 lm
912300023795	BVP651 LED750-4S/740 DM10 ALU PSU	63080 lm
912300023796	BVP651 LED750-4S/740 DW10 ALU PSU	63840 lm
912300023797	BVP651 LED750-4S/740 DX10 ALU PSU	60800 lm
912300023798	BVP651 LED750-4S/740 DX50 ALU PSU	61560 lm
912300023799	BVP651 LED750-4S/740 DX51 ALU PSU	37240 lm
912300023961	BVP651 LED450-4S/740 DX60 ALU PSU	40050 lm
912300023962	BVP651 LED500-4S/740 DX60 ALU PSU	44000 lm
912300023963	BVP651 LED550-4S/740 DX60 ALU PSU	49280 lm
912300023964	BVP651 LED600-4S/740 DX60 ALU PSU	52800 lm
912300023965	BVP651 LED650-4S/740 DX60 ALU PSU	58080 lm
912300023966	BVP651 LED700-4S/740 DX60 ALU PSU	61600 lm
912300023967	BVP651 LED750-4S/740 DX60 ALU PSU	66880 lm
912300024506	BVP651 LED800-4S/740 PSU DX60 ALU	69600 lm
912300024507	BVP651 LED800-4S/740 PSU DX51 ALU	39200 lm
912300024508	BVP651 LED800-4S/740 PSU DX50 ALU	64000 lm
912300024509	BVP651 LED800-4S/740 PSU DX10 ALU	63200 lm
912300024510	BVP651 LED800-4S/740 PSU OFA52 ALU	66400 lm
912300024511	BVP651 LED800-4S/740 PSU S ALU	67200 lm
912300024512	BVP651 LED800-4S/740 PSU DM10 ALU	65600 lm
912300024513	BVP651 LED800-4S/740 PSU DW10 ALU	66400 lm

Mechanical and Housing

Order Code	Full Product Name	Color	Order Code	Full Product Name	Color
912300023731	BVP651 LED450-4S/740 S ALU PSU	Gray	912300023763	BVP651 LED650-4S/740 DX10 ALU PSU	Gray
912300023732	BVP651 LED450-4S/740 OFA52 ALU PSU	Gray	912300023764	BVP651 LED650-4S/740 DX50 ALU PSU	Gray
912300023733	BVP651 LED450-4S/740 DM10 ALU PSU	Gray	912300023765	BVP651 LED650-4S/740 DX51 ALU PSU	Gray
912300023734	BVP651 LED450-4S/740 DW10 ALU PSU	Gray	912300023766	BVP651 LED700-4S/740 S ALU PSU	Gray
912300023735	BVP651 LED450-4S/740 DX10 ALU PSU	Gray	912300023767	BVP651 LED700-4S/740 OFA52 ALU PSU	Gray
912300023736	BVP651 LED450-4S/740 DX50 ALU PSU	Gray	912300023768	BVP651 LED700-4S/740 DM10 ALU PSU	Gray
912300023737	BVP651 LED450-4S/740 DX51 ALU PSU	Gray	912300023769	BVP651 LED700-4S/740 DW10 ALU PSU	Gray
912300023738	BVP651 LED500-4S/740 S ALU PSU	Gray	912300023770	BVP651 LED700-4S/740 DX10 ALU PSU	Gray
912300023739	BVP651 LED500-4S/740 OFA52 ALU PSU	Gray	912300023771	BVP651 LED700-4S/740 DX50 ALU PSU	Gray
912300023740	BVP651 LED500-4S/740 DM10 ALU PSU	Gray	912300023772	BVP651 LED700-4S/740 DX51 ALU PSU	Gray
912300023741	BVP651 LED500-4S/740 DW10 ALU PSU	Gray	912300023793	BVP651 LED750-4S/740 S ALU PSU	Gray
912300023742	BVP651 LED500-4S/740 DX10 ALU PSU	Gray	912300023794	BVP651 LED750-4S/740 OFA52 ALU PSU	Gray
912300023743	BVP651 LED500-4S/740 DX50 ALU PSU	Gray	912300023795	BVP651 LED750-4S/740 DM10 ALU PSU	Gray
912300023744	BVP651 LED500-4S/740 DX51 ALU PSU	Gray	912300023796	BVP651 LED750-4S/740 DW10 ALU PSU	Gray
912300023745	BVP651 LED550-4S/740 S ALU PSU	Gray	912300023797	BVP651 LED750-4S/740 DX10 ALU PSU	Gray
912300023746	BVP651 LED550-4S/740 OFA52 ALU PSU	Gray	912300023798	BVP651 LED750-4S/740 DX50 ALU PSU	Aluminum
912300023747	BVP651 LED550-4S/740 DM10 ALU PSU	Gray	912300023799	BVP651 LED750-4S/740 DX51 ALU PSU	Gray
912300023748	BVP651 LED550-4S/740 DW10 ALU PSU	Gray	912300023961	BVP651 LED450-4S/740 DX60 ALU PSU	Gray
912300023749	BVP651 LED550-4S/740 DX10 ALU PSU	Gray	912300023962	BVP651 LED500-4S/740 DX60 ALU PSU	Gray
912300023750	BVP651 LED550-4S/740 DX50 ALU PSU	Gray	912300023963	BVP651 LED550-4S/740 DX60 ALU PSU	Gray
912300023751	BVP651 LED550-4S/740 DX51 ALU PSU	Gray	912300023964	BVP651 LED600-4S/740 DX60 ALU PSU	Gray
912300023752	BVP651 LED600-4S/740 S ALU PSU	Gray	912300023965	BVP651 LED650-4S/740 DX60 ALU PSU	Gray
912300023753	BVP651 LED600-4S/740 OFA52 ALU PSU	Gray	912300023966	BVP651 LED700-4S/740 DX60 ALU PSU	Gray
912300023754	BVP651 LED600-4S/740 DM10 ALU PSU	Gray	912300023967	BVP651 LED750-4S/740 DX60 ALU PSU	Gray
912300023755	BVP651 LED600-4S/740 DW10 ALU PSU	Gray	912300024506	BVP651 LED800-4S/740 PSU DX60 ALU	Aluminum
912300023756	BVP651 LED600-4S/740 DX10 ALU PSU	Gray	912300024507	BVP651 LED800-4S/740 PSU DX51 ALU	Aluminum
912300023757	BVP651 LED600-4S/740 DX50 ALU PSU	Gray	912300024508	BVP651 LED800-4S/740 PSU DX50 ALU	Aluminum
912300023758	BVP651 LED600-4S/740 DX51 ALU PSU	Gray	912300024509	BVP651 LED800-4S/740 PSU DX10 ALU	Aluminum
912300023759	BVP651 LED650-4S/740 S ALU PSU	Gray	912300024510	BVP651 LED800-4S/740 PSU OFA52 ALU	Aluminum
912300023760	BVP651 LED650-4S/740 OFA52 ALU PSU	Gray	912300024511	BVP651 LED800-4S/740 PSU S ALU	Aluminum
912300023761	BVP651 LED650-4S/740 DM10 ALU PSU	Gray	912300024512	BVP651 LED800-4S/740 PSU DM10 ALU	Aluminum
912300023762	BVP651 LED650-4S/740 DW10 ALU PSU	Gray	912300024513	BVP651 LED800-4S/740 PSU DW10 ALU	Aluminum

