


BREEZE T5

Recessed Luminaire



Breeze 414 F41



Breeze 414 F41 9CR

Type:	Recessed T5 luminaire with a choice of louvres for most applications.
Specification:	There are two types of louvres in the range: specular parabolic with mirror cross blades and with ribbed cross blades. Louvre is fitted into the body with a locking safety clip for maximum stability. Number of cross blades is optional from 5 to 11 for better glare protection. Fully enclosed painted steel body, wiring is concealed and not visible from ground level. Luminaire is plastic-wrapped and packaged in twin boxes.
Installation:	Fits 15–24 mm exposed T-Bar ceilings 600×600 mm. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use support brackets.
Application:	Office buildings, shops and other commercial environments.



To fit plasterboard and/or 625×625 mm suspended ceiling (Germany market) could be designed. For more information, see Option list.

SB – Support brackets (4 pcs) for installation into a plasterboard ceiling. Available on request.

Type	Lamp (W) and holder	Overall dimensions, mm	Weight, kg	Total wattage, W
Breeze 214 I25	2×14 (G5)	295×595×85	2,2	31
Breeze 224 I26	2×24 (G5)	295×595×85	2,2	49
Breeze 314 K27	3×14 (G5)	595×595×72	2,8	46
Breeze 314 K27 7CR	3×14 (G5)	595×595×72	2,8	46
Breeze 314 K27 9CR	3×14 (G5)	595×595×72	2,8	46
Breeze 324 K34	3×24 (G5)	595×595×72	3,05	73
Breeze 324 K34 9CR	3×24 (G5)	595×595×72	3,05	73
Breeze 414 F41	4×14 (G5)	595×595×72	2,9	62
Breeze 414 F41 7CR	4×14 (G5)	595×595×72	2,9	62
Breeze 414 F41 9CR	4×14 (G5)	595×595×72	2,9	62
Breeze 414 F41 11CR	4×14 (G5)	595×595×72	2,9	62
Breeze 424 F08	4×24 (G5)	595×595×72	3,15	98
Breeze 424 F08 9CR	4×24 (G5)	595×595×72	3,15	98
Breeze 228 I27	2×28 (G5)	295×1195×85	3,2	60
Breeze 254 I28	2×54 (G5)	295×1195×85	3,2	115
Breeze 328 K30	3×28 (G5)	595×1195×85	5,7	90
Breeze 354 K31	3×54 (G5)	595×1195×85	5,7	172,5
Breeze 428 I29	4×28 (G5)	595×1195×85	5,7	120
Breeze 454 I30	4×54 (G5)	595×1195×85	5,7	230

Options available on request:

- DIM – Dimmable ballast 1-10V
- SWITCHDIM – Switch DIM ballast
- DALI – DALI ballasts
- EMG – Emergency version 1 hour
- EM2 – Emergency version 2 hours
- EM3 – Emergency version 3 hours
- 4TB – 4 way terminal block for loop feed and ease of wiring
- 5TB – 5 way terminal block for loop feed and ease of wiring
- MAT – Matt reflector
- MBL – Matt cross blades
- RIB – Ribbed cross blades
- 7CR – Louvre with 7 cross blades
- 9CR – Louvre with 9 cross blades
- 11CR – Louvre with 11 cross blades
- 24CR – Louvre with 24 cross blades (2/4×28/54 W)
- W625 – Designed specifically for the German market to fit 625×625 suspended ceiling or plasterboard

BREEZE 414 F41 9CR

